

# Concreto

6 COLOURS / 8 SIZES / 3 THICKNESSES / 2 FINISHES / **VARIOUS** SPECIAL PIECES

The Concreto collection offers a porcelain surface that recalls an industrial design, with a clear reference to the neutral beauty of concrete and the minimalism of modern architecture.

With 6 natural colours, many formats and thicknesses including 20mm suitable for outdoor installation, Concreto provides industrial beauty in every space.




Concreto



Concreto



# Concreto



ANTHRACITE



DOVE



GREY



SAND



IVORY



WHITE



WEAVE DECOR AVAILABLE IN ALL COLOURS

Porcelain	6mm thick		8mm thick		20mm thick	Wall/floor	Interior/exterior
	Matt R10 A+B	Grip R11 A+B+C	Matt R10 A+B	Grip R11 A+B+C	Grip R11 A+B+C	All tiles	All tiles
300x600			✓	✓		Wall & Floor	Interior & Exterior
600x600			✓	✓	✓	Wall & Floor	Interior & Exterior
600x1200			✓	✓	✓	Wall & Floor	Interior & Exterior
750x750	✓					Wall & Floor	Interior & Exterior
750x1500	✓					Wall & Floor	Interior & Exterior
1000x1000	✓	✓				Wall & Floor	Interior & Exterior
150x150 Weave			✓			Wall & Floor	Interior & Exterior
600x600 Weave			✓			Wall & Floor	Interior & Exterior
600x1200 Weave			✓			Wall & Floor	Interior & Exterior

Mosaics, step pieces and skirting also available, please enquire.

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

# Concreto

GROUP / BLA - PORCELAIN

	Standard	Requirement	Established Values
Length and Width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water Absorption	ISO 10545-3	$E_b \leq 0.5\%$	$E_b \leq 0.5\%$
Breaking Strength	ISO 10545-4	$\geq 1300N$	$\geq 1300N$
Modulus of Rupture	ISO 10545-4	Ave Minimum 35 N/mm <sup>2</sup>	Ave Minimum 42 N/mm <sup>2</sup>
Resistance to deep abrasion (unglazed tiles)	ISO 10545-6	$\leq 175mm^2$	$\leq 140 mm^2$
Thermal Shock Resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class UB	UB
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	UHB
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	ULB
Resistance to Stain	ISO 10545-14	Declare Value	Class 5
Reaction to Fire		Class A1 A1/FL	Class A1/FL

Slip Resistance Characteristics	Pendulum Dry (4S Slider 96) +36	Pendulum Wet (4S Slider 96) +36
Full Range	✓	✓

Recycled Content	25 %
Range Name	Concreto

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: [www.parkside.co.uk](http://www.parkside.co.uk) – E: [info@parkside.co.uk](mailto:info@parkside.co.uk)

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles