

Lenton

18 COLOURS / 1 SIZE / 1 FINISH

Variations in colour and patterning create interplays of light which add vibrancy to spaces. Brick tile Lenton introduces a collection with a decidedly contemporary appeal and ultra-glossy, flawed surfaces in 18 shades.




Lenton



Lenton



Lenton



LIQUORICE



BRONZE



FOREST GREEN



INK BLUE



OCHRE



ANTIQUE WHITE



BLUE



GREEN



GREIGE



MUSK



WHITE



OFF-WHITE



PINK



BEIGE



TURQUOISE



WOODLAND



CHINA BLUE



TAUPE



60x240

Porcelain 60x240x10

Gloss

Wall & Floor

Interior & Exterior

Lenton

GROUP / BLa - PORCELAIN

	Standard	Requirement	Established Values
Length and Width	ISO 10545-2	±0.6% - ±2mm	Conforms
Thickness	ISO 10545-2	±5% - ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% - ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% - ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% - ±2.0mm	Conforms
Water Absorption	ISO 10545-3	$E_w \leq 0.5\%$	$\leq 0.5\%$
Breaking Strength	ISO 10545-4	$\geq 1300N$	$\geq 1300N$
Modulus of Rupture	ISO 10545-4	Ave Minimum 35 N/mm ²	35 N/mm ²
Thermal Shock Resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	GHB
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLB
Resistance to Stain	ISO 10545-14	Declare Value	Class 5
Reaction to Fire		Class A1 A1/FL	Class A1

Recycled Content	10 %
Range Name	Lenton

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles