

Tez

7 COLOURS / 7 SIZES / 3 FINISHES

Tez is a stylish terrazzo effect with rich colourways, creating a statement in any space. With sizes ranging from 20x20cm to 120x120cm, with polished, matt and PTV+36 finishes, this is a staple range with many different uses. If you're after a sophisticated pattern instead of the bold colourways, there is also a selection of monochromatic patterned designs in a PTV+36 20x20cm format.




Tez



Tez



Tez



ZETTA



QUETTA



ATTO



YOTTO



MUON

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Tez

Porcelain	10mm thick			Wall/floor	Interior/exterior
	Matt	Polished	PTV+36	All tiles	All tiles
200x200	✓		✓	Wall & Floor	Interior & Exterior
300x300 Mosaic	✓			Wall & Floor	Interior & Exterior
520x600 Hex	✓			Wall & Floor	Interior & Exterior
590x590	✓			Wall & Floor	Interior & Exterior
800x800			✓	Wall & Floor	Interior & Exterior
1190x1190		✓		Wall & Floor	Interior & Exterior
1200x1200	✓			Wall & Floor	Interior & Exterior

GROUP / BLA - PORCELAIN

	Standard	Requirement	Established Values
Length and Width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water Absorption	ISO 10545-3	$E_b \leq 0.5\%$	$\leq 0.5\%$
Breaking Strength	ISO 10545-4	$\geq 1300N$	$\geq 1300N$
Modulus of Rupture	ISO 10545-4	Ave Minimum 35 N/mm ²	35 N/mm ²
Resistance to deep abrasion (glazed tiles)	ISO 10545-7	Declare Value	PEI 3
Thermal Shock Resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Pass
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Pass
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class GB	GA
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	NPD
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	GLB
Resistance to Stain	ISO 10545-14	Declare Value	Class 4
Reaction to Fire		Class A1 A1/FL	Class A1/FL

Slip Resistance Characteristics	Pendulum Dry (4S Slider 96) +36	Pendulum Wet (4S Slider 96) +36
Full Range	✓	✓

Recycled Content	41 %
Range Name	Tez