

Arezzo

3 COLOURS / 4 SIZES / 5 FINISHES

Arezzo is inspired by Versilia Marble which is quarried in the Apuan Alps of Tuscany, known for its extraordinary variety of veining and hues. With 3 colours and sizing ranging from 60x60cm up to 120x278cm, Arezzo is best appreciated in full coverage. Finishes varying from Silky, to Lappato, to Fluted, to PTV+36 options mean there's an option for every commercial space.



Arezzo



Arezzo



Arezzo



FIORITO IVORY



BARDIGLIO SILVER



NUVOLATO GREY

Porcelain	6mm thick		9mm thick				Wall/floor	Interior/exterior
	Silky	Silky	Lappato	R10	R11	Fluted	All tiles	All tiles
1200x2780	✓						Wall & Floor	Interior & Exterior
1200x1200		✓					Wall & Floor	Interior & Exterior
600x1200		✓	✓	✓	✓	✓	Wall & Floor	Interior & Exterior
600x600		✓					Wall & Floor	Interior & Exterior

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles

Arezzo

GROUP / BLA - PORCELAIN

	Standard	Requirement	Established Values
Length and Width	ISO 10545-2	±0.6% ~ ±2mm	Conforms
Thickness	ISO 10545-2	±5% ~ ±0.5mm	Conforms
Straightness	ISO 10545-2	±0.5% ~ ±1.5mm	Conforms
Flatness	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Rectangularity	ISO 10545-2	±0.5% ~ ±2.0mm	Conforms
Water Absorption	ISO 10545-3	$E_b \leq 0.5\%$	$E_b \leq 0.5\%$
Breaking Strength	ISO 10545-4	$\geq 1300N$	$\geq 1300N$
Modulus of Rupture	ISO 10545-4	Ave Minimum 35 N/mm ²	Ave Minimum 40 N/mm ²
Resistance to deep abrasion (unglazed tiles)	ISO 10545-6	$\leq 175mm^2$	$\leq 150mm^2$
Thermal Shock Resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Pass according to EN ISO 10545-1	Resistant
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Min Class UB	UB
Resistance to high concentrations of alkalis and acids	ISO 10545-13	Declare Value	UHC
Resistance to low concentrations of alkalis and acids	ISO 10545-13	Declare Value	ULC
Resistance to Stain	ISO 10545-14	Declare Value	Complies
Reaction to Fire		Class A1 A1/FL	Class A1/FL

Slip Resistance Characteristics	Pendulum Dry (4S Slider 96) +36	Pendulum Wet (4S Slider 96) +36
Full Range	✓	✓

Recycled Content	0 %
Range Name	Arezzo

The colour representations shown in this data sheet are as accurate as the limitations of the printing process will allow. Due to the manufacturing process of our floor tiles there may be a small variation in the PTV value. The slip resistance values are correct at the time of testing and represent the standard production value. Inadequate cleaning and maintenance will lead to significant reduction in the slip resistance of any tiles. The pendulum test results have been displayed in line with H&S Executive guidelines whereby 0-24 represents high slip potential, 25-35 moderate slip potential & 36+ represents a low slip potential.

For further information contact: T: 0116 276 2532 – W: www.parkside.co.uk – E: info@parkside.co.uk

Strata Technical Tiles is the partner brand of Parkside Architectural Tiles